

HC

Corrugated Hard Suction Hose



The corrugated cover provides extra flexibility and reduces weight, while the hose itself is reinforced to prevent collapse. Outer cover is made of long wearing synthetic rubber.

CONSTRUCTION: Corrugated cover, reinforced with multiple plies of fabric and helix spring steel wire. Outer cover - synthetic rubber.

APPLICATIONS: Heavy duty suction hose for fire engines.

PERFORMANCE FEATURES: Corrugated cover provides extra flexibility, Helix prevents collapse. Long wearing - ozone resistant construction. Furnished with soft ends.

SIZES / PRESSURES & VACUUM RATINGS:

| SIZE | WORKING PRESSURE | BAR | VACUUM RATING |
|--------|------------------|-----|---------------|
| 2-1/2" | 150 PSI | 10 | 27 |
| 3" | 150 PSI | 10 | 27 |
| 3-1/2" | 150 PSI | 10 | 27 |
| 4" | 150 PSI | 10 | 27 |
| 4-1/2" | 150 PSI | 10 | 27 |
| 5" | 150 PSI | 10 | 27 |
| 6" | 125 PSI | 9 | 27 |

STANDARD LENGTHS: 10' - Up to 50' available.

WEIGHTS: 10' Length, uncoupled

| SIZE | POUNDS | KG |
|--------|--------|------|
| 2-1/2" | 14 | 6.3 |
| 3" | 17 | 7.7 |
| 3-1/2" | 20 | 9.1 |
| 4" | 23 | 10.4 |
| 4-1/2" | 31 | 14.1 |
| 5" | 40 | 18.2 |
| 6" | 47 | 21.4 |

HL

Hard Suction Hose



A light duty wire reinforced hose. Outer cover is made from long wearing synthetic rubber.

CONSTRUCTION: Hose is wire reinforced. Several plies polyester and dual spring steel helix. Outer cover is synthetic rubber.

APPLICATIONS: Fire engine suction hose for light duty applications. Also good for general water hose use under pressure.

PERFORMANCE FEATURES: Abrasion and ozone resistant. Temp rating of -40° F to 180° F.

SIZES / PRESSURES & VACUUM RATINGS:

| SIZE | WORKING PRESSURE | BAR | VACUUM RATING |
|--------|------------------|-----|---------------|
| 1-1/2" | 250 PSI | 17 | 30 |
| 2" | 200 PSI | 14 | 30 |
| 2-1/2" | 150 PSI | 10 | 30 |
| 3" | 125 PSI | 9 | 30 |

STANDARD LENGTHS: 10'

WEIGHTS: 10' Length, uncoupled

| SIZE | POUNDS | KG |
|--------|--------|-----|
| 1-1/2" | 6 | 2.7 |
| 2" | 11 | 5 |
| 2-1/2" | 15 | 6.8 |
| 3" | 17 | 7.7 |

Heavy duty, wire reinforced hard suction hose for pump suction service on fire engines.

CONSTRUCTION: Hose is wire reinforced. Multiple plies of fabric and helix spring steel wire. Outer cover is synthetic rubber.

APPLICATIONS: Pump suction service on fire engines.

PERFORMANCE FEATURES: Long wearing - ozone resistant construction. Helix prevents collapse. Furnished with soft ends.

SIZES / PRESSURES & VACUUM RATINGS:

| SIZE | WORKING PRESSURE | BAR | VACUUM RATING |
|--------|------------------|-----|---------------|
| 2-1/2" | 150 PSI | 10 | 27 |
| 3" | 150 PSI | 10 | 27 |
| 3-1/2" | 150 PSI | 10 | 27 |
| 4" | 150 PSI | 10 | 27 |
| 4-1/2" | 150 PSI | 10 | 27 |
| 5" | 150 PSI | 10 | 27 |
| 6" | 125 PSI | 9 | 27 |

STANDARD LENGTHS: Up to 50' available

WEIGHTS: 10' Length, uncoupled

| SIZE | POUNDS | KG |
|--------|--------|------|
| 2-1/2" | 16 | 7.3 |
| 3" | 20 | 9 |
| 3-1/2" | 24 | 11 |
| 4" | 28 | 12.7 |
| 4-1/2" | 37 | 16.8 |
| 5" | 52 | 23.6 |
| 6" | 61 | 27.7 |

HS
Heavy Duty Hard Suction



A lightweight yet flexible hose that can safely handle pressure up to 800 PSI. The outer cover is designed to withstand the weathering and abrasion associated with severe service. Two braid reinforced for strength.

CONSTRUCTION: Vertical braid construction with ozone resistant cover.

APPLICATIONS: Safely handles pressure at 800 PSI. Severe service fire engine booster hose.

PERFORMANCE FEATURES: Lightweight, flexible. Cover withstands weathering and abrasion. Two braid reinforced.

SIZES / PRESSURES & VACUUM RATINGS:

| SIZE | WORKING PRESSURE | BAR |
|------|------------------|-------|
| 3/4" | 800 PSI | 55.17 |
| 1" | 800 PSI | 55.17 |

STD. LENGTHS: 100' available

WEIGHTS: 100' Length, uncoupled

| SIZE | POUNDS | KG |
|------|--------|----|
| 3/4" | 50 | 23 |
| 1" | 68 | 31 |

BH
Booster Hose



217 Titusville Road
Union City, Pennsylvania 16438-8698 USA
PH: 814-438-7616 FAX: 814-438-8163
1-800-447-HOSE
e-mail: hose_sales@snap-tite.com
www.snap-titehose.com



Industrial Estate
Whitemill - Wexford
Republic of Ireland
PH: 353-53-41566 FAX: 353-53-41582
e-mail: snaptite@snap-tite.iol.ie
www.snap-tite.com

ISO-9001 Certified

03-0023BE-1101