



PNEUMATIC DECON-SHOWER

For fast decontamination of protective workgear after hazardous materials missions. The DECON tub is large enough to prevent contaminated spraywater spattering onto the surrounding ground.

ADVANTAGES:

- Long life
- Lightweight
- Quickly transported and assembled on site
- Low air requirement
- Self-erecting

SAFETY:

- Low operating pressure of maximum 0.5 bar (7.25 psi)
- Integrated safety valve, 0.5 bar, to prevent over-inflation of the tent
- Tear-proof material
- Highly resistant

MATERIAL:

Supporting frame: polyamide fabric, neoprene-coated on both sides

Decon tub: polyester fabric, PVC-coated on both sides

Materials list (See pp 72/73)

COMPLETE SET:

Set Pneumatic DECON Shower
Art.-No.: 152 13 000

Consisting of:

Pneumatic tub stiffening frame
0.5 bar (7.25 psi)

PVC tub sheeting with velcro fastener

Shower hose

Shower hood

Portable valise

Repair Kit

Packaged size:
110 x 72 x 30 cm
(43 x 28 x 12 in.)

Weight: 33 kg (72,7 lbs)

TECHNICAL DATA:

Type	Pneumatic Decon Shower	
Art.-No. (standard equipment)	152 13 000	
Size tub: exterior (l x w x h)	cm	300 x 168 x 30
	in.	118 x 66 x 12
Size tub: interior (l x w x h)	cm	240 x 108 x 30
	in.	94 x 42 x 12
Height	cm	209
	in.	92.1
Operating pressure	bar	0.5
	psi	7.25
Test pressure	bar	0.65
	psi	9.4
Nominal content	l	900
	cu.ft.	31.8
Air requirement	l	1,350
	cu.ft.	47.7
Capacity	l	770
	cu.ft.	27.2
Weight	kg	33
	lbs	72.7

Decon Shower

Art.-No.: 152 20 300

Consisting of:

Screwable sections of plastic piping for use with DECON tub

Art.-No.: 152 20 301

Valise

Art.-No.: 152 20 310

Shower curtain

Art.-No.: 152 20 320

Packaged size:

130 x 40 x 20 cm

(51 x 16 x 9 in.)

Weight: 17 kg (37 lbs)

