

THE OCENCO M-20.2



THE PREFERRED SOLAS EEBOOLUTION SOLAS II-2

*Emergency Escape Breathing Device



SOLAS TRAINING PACKAGE

M-20.2T Trainer, manual and video- Trainer comes complete with extra mouthpieces, in a light blue secondary container.
Teaches proper use of the unit. Ask your Ocenco

outh-

M-20.2 Storage bracket

representative for

details.

Bright orange welded steel bracket with quick opening Velcro closure.



Product No.: 648061

Since 1970, Ocenco has been ecognized around the globe as a leader in safety equipment used in hostile and hazardous environments. Every Ocenco product is designed to achieve superior performance under the most demanding conditions.



Product No.: 940066



For all your fire, safety & emergency response needs.
Phone 08 9331 8788
Fax 08 9331 7977
www.mercfire.com.au

© 2000 All rights reserved. 8-00-2M

OCENCO M-20.2 EEBD

 PROVEN COMPRESSED OXYGEN TECHNOLOGY

SUPERIOR PERFORMANCE

15-YEAR SERVICE LIFE

 ISO CERTIFIED TRAINING PROGRAM

WORLD WIDE APPROVALS

...and there is more:



156,864 M-20.2 EEBDs on board Navy and Coast Guard ships around the world verify the superior design and performance of the Ocenco M-20.2.

UNMATCHED BENEFITS

15-Year Service Life The M-20.2 is certified for 15 years service.

Maintenance-Free for 15 Years The M-20.2 requires only visual inspection by shipboard personnel once every two years.

SOLAS II-2 REGULATION 13 The M-20.2 and the Training Package are SOLAS Compliant for 15 years, in any port in the world.

Robust Design The sealed watertight case protects against harsh marine conditions.

Superior Performance Automatic activation, complete protection from life threatening atmospheres and the highest respiratory protection factor available.

THE OCENCO M-20.2 EEBD CAN BE DONNED IN SECONDS; simply unlatch the case, pull out the unit, and insert the mouthpiece and nose clip. The attached hood can be donned at anytime during the escape. The mouthpiece and nose clip combination allows the Ocenco M-20.2 EEBD to be donned in a smoke filled environment.







STORAGE TEMPERATURE RANGE -20°C TO 65°C (-4°F TO 149°C) SERVICE LIFE 15 YEARS OXYGEN DELIVERY SYSTEM AUTOMATIC ON, COMPRESSED OXYGEN, DEMAND REGULATED INSPECTION VISUAL INSPECTION EVERY TWO YEARS BY SHIPBOARD PERSONNEL M-20.2 ASSEMBLY

M-20.2 EEBD - 17 X 17 X 7.6 CM (6.8 X 6.8 X 3 IN)
SECONDARY CONTAINER (INCLUDED WITH UNIT) - 21 X 23 X 10 CM

M-20.2 PHYSICAL CHARACTERISTICS AND PERFORMANCE DATA

LLOYDS REGISTER, ABS, CE 194/EN400, NIOSH

15-32 MINUTES

1.4 KG (3.1 LBS)

THE OCENCO M-20.2 EEBD HAS BEEN SELECTED FOR EXCLUSIVE USE BY

THE US NAVY, US COAST GUARD, HELLENIC NAVY AND THE ITALIAN NAVY,



Relief valve



Oxygen cylinde







Teflon hood

